



# Hydraulic Leveling Leg Systems

Let the Fab Tec Hydraulic Leveling System do the heavy lifting and leveling of your carrier as a 'plant mounted' system on your new Fab Tec portable plant, or as a kit installed on your existing equipment.

## Standard Features

- 6" bore cylinders have 70,000# capacity with 18" stroke.
- 3/4" plate x 12" x 12" foot pads.
- Heavy duty mounting brackets.
- Individual spool valve control for each cylinder.
- Delta HPX-200 hydraulic power unit with 12V DC motor.



The Fab Tec 12VDC Leveling System in 2, 4, and 6 leg configurations —

— available plant mounted and ready to go, or as a kit.



# **FAB/TEC Inc. Hydraulic Leveling Control Options**

## *12 V Continuous Duty Motor*

The special built power unit with Marathon 1 hp 12V continuous duty motor is constant rpm/ constant torque for dependable lifting and leveling .

The continuous duty power is a robust alternative to the standard 12 volt "starter" motor as it can run until the battery is dead with no dam-

- 1 HP Marathon 12V CD motor
- 2 stage pump delivers 3 1/2 gpm first stage power, then 7/8 gpm at 2nd stage.



## *Honda GX-240 Gas Powered Pump*

The standard Honda GX- 240 is one of the best all-around solutions and is well suited to fast set-ups, running large cylinders, or used on multiple plants with quick disconnects.

- Heavy duty enclosure with isolation mounts.
- 8 HP Honda engine with electric key start .
- 12 gallon tank with sight gauge and filter protection.
- 2 1/2 GPM pump.

